



FROM 

ALUMINUM FINISHING TAPE

- » *Creates A Finished Look*
- » *Covers All Butyl Seams*
- » *Great For Attaching Wiring*
- » *Keeps Your Pants Clean!*

APPLICATIONS



SEAL SEAMS



FILL HOLES



ATTACH WIRES



CLEAN TRANSITIONS



Dynamat® DynaTape™ Aluminum Finishing Tape



DynaTape is a 1 1/2" wide, 2 mil aluminum finishing tape. It can be used with Dynamat to seal seams, fill holes, attach wiring, contain unwanted butyl migration and give your project a complete and professional appearance. DynaTape's transparent, pressure sensitive acrylic adhesive makes finishing your project a simple process, providing you with a cool, quiet and comfortable ride.



AUTOMOTIVE SERIES

DYNA TAPE



DESCRIPTION

DynaTape® is a performance grade aluminum foil tape coated with an acrylic adhesive system. Meets both UL 181A-P and UL 1818-FX standards.

APPLICATIONS

DynaTape® is a dual use product designed for use as a seal and to ensure the integrity of seams and joints on both fiberglass and sheet metal.

PERFORMANCE FEATURES

- Conformable aluminum foil backing provides easy handling and efficient application
- High performance acrylic adhesive system provides exceptional adhesion in a wide range of temperature, heat, and humidity conditions
- Product is hand tear-able for easy application on the job site

INSTALLATION

Pressure sensitive acrylic, peel and stick adhesive.

SPECIFICATIONS

Backing Type

Aluminum Foil

Total Thickness

4.3 mil

0.11 mm

Adhesion to Steel

Exceeds 60 (oz/in) width

Exceeds 16.42 (N/25.4mm)

Shear Adhesion: 50% RH

40° F (4.44° C)

Exceeds 6 Hours

73.4° F (23° C)

Exceeds 6 Hours

150° F (65.56° C)

Exceeds 6 Hours

Tensile

Exceeds 25 (lbs/in) width

Exceeds 109.45 (N/25.4 mm)

Adhesive System

Solvent Acrylic

Operating Temp. Range

-20° F to 350° F

-29° C to 177° C

50,000 Cycle Test

No Rupture

